

COMPATIBILITY CHART ANTIFOULING Sea-Line®

NEW PAINT SEA-LINE®

SELF-POLISHING
ANTIFOULING

SELF-POLISHING
ANTIFOULING
ALU PLUS

HARD
ANTIFOULING

SEAGUARD
fouling stop

CURRENT COAT ANTIFOULING (only in good condition)	SEA-LINE®	<ul style="list-style-type: none"> SELF-POLISHING SELF-POLISHING ALU PLUS HARD SEAGUARD 				
	INTERNATIONAL	<ul style="list-style-type: none"> MICRON EXTRA MICRON EXTRA 2 CRUISER UNO CRUISER BRIGHT WHITE INTERSPEED ULTRA 2 VC OFSHORE EU 				
		<ul style="list-style-type: none"> MICRON OPTIMA VC 17m EXTRA TRILUX 33 				
	HEMPEL	<ul style="list-style-type: none"> Ocean Performer Mille Dynamic Hard Racing Cruising Performer/ Tiger Cruising Glide Cruise Tiger Extra / Titan ultra 				
		<ul style="list-style-type: none"> Hard Racing Ultra 				
	SEA JET	<ul style="list-style-type: none"> 031 (Samurai) 033 (Shogun) 034 (Emperor) 037 (Costal) 039 (Platinum) 				
	OTHER	<ul style="list-style-type: none"> OLIVA VSE PLASTIMO Classic PLASTIMO Performance PLASTIMO Racing SOROMAP AF1 SOROMAP AF2 SOROMAP AFC+ 				

Do not risk !

If existing antifouling coat is in Bad condition, remove it !

Basic recommendation for surface preparation and paint application Sea-Line® :

	<ul style="list-style-type: none"> Clean old surface with water under pressure (remove splinters and repair damage on the surface) Abrade P100-P240 all surface places after repair or grinded surfaces from antifouling paint protect using 1K UNIVERSAL PRIMER Sea-Line® Apply 1-3 layers of Sea-Line antifouling
	<ul style="list-style-type: none"> Remove all layers of old antyfoiling Abrade P100-P240 all surface Apply minimum 1 layer primer: <ul style="list-style-type: none"> 2K Epoxy Lightprimer 5:1 Sea-Line® - laminates (GRP) 2K Epoxy Anticorrosive 4:1 Sea-Line® - steel, aluminium 2K Epoxy Woodprimer 10:4 Sea-Line® - wood 1K UNIVERSAL PRIMER Sea-Line® - laminates (GRP), steel, wood Apply by 1-3 of layers Sea-Line antifouling
	<ul style="list-style-type: none"> ➤ Use biocides safely. Always read the label and product information before use ➤ When using the product in a small, enclosed space you must provide forced ventilation ➤ Avoid contact of liquid with eyes and skin ➤ Please follow safety instructions from the technical data sheet for hazardous chemical and follow Polish workplace safety laws